


TIG 200 PFC

Šifra artikla: **ET-200**

Karakteristike

- Robustan, ergonomski dizajn
- ClearVision tehnologija za jasnu vidljivost parametara
- Širok raspon ulaznog napona – idealno za gradilišta i servisne terene
- **Dash-Arc** - visokofrekventni TIG (HF)
- **Smart Lift TIG** – čist start luka bez kontaminacije elektrode
- Sve karakteristike DC TIG parametara
- Modul za prijem daljinske kontrole (opcija)
- Power Factor Correction (PFC) – manja potrošnja, bolje ponašanje na dužim kablovima
- Brzi fabrički reset i auto-sleep mod
- **ABAP**: sistem za balansiran protok zraka (duži vijek ventilacije)
- **Smart gas** - za optimiziranje potrošnje gasa
- **Fan on demand** – ventilator radi samo kada je potrebno
- VRD sigurnosna zaštita u MMA modu
- Zaštita od pregrijavanja i preopterećenja
- **Isporučuje se sa zaštitnim koferom i MMA kablovima**



Tehnički Podaci

ET-200		TIG 200 PFC	
Ulazni napon		AC95-265V, 50/60 Hz	
Napon bez opterećenja		AC 115V	AC 230V
TIG	Nazivna ulazna struja	29.7A	19.5A
	Efektivna struja (I _{eff})	14.9A	9.8A
	Nazivna ulazna snaga	3.4kVA	4.5kVA
	Opseg struje	5-160A	5-200A
	Radni ciklus @ 40°C	25%	
MMA	Nazivna ulazna struja	31.6A	25.6A
	Efektivna struja (I _{eff})	15.8A	12.8A
	Nazivna ulazna snaga	3.7kVA	5.9kVA
	Opseg struje	10-120A	10-180A
	Radni ciklus @ 40°C	25%	
Efikasnost		84%	
Faktor snage		0.99	
Potrošnja u stanju mirovanja		MMA: 33W TIG: 7W	
Klasa zaštite		IP23S	
Klasa izolacije		H	
Dimenzije (DxŠxV)		453 x 150 x 313mm	
Težina		8.97Kg	
Preporučena snaga agregata		5kVA	7kVA

* agregat mora imati AVR regulator



Standardna Oprema

Kofer
MMA kablovi 3m dužine
TIG gorionik 4m
Crijevo za gas

Opcionalna Oprema

Bežični daljinski
Žični daljinski
Bežični nožni prekidač
Žični nožni prekidač