



MIG 200 PFC

Šifra artikla: **EM-200C**



Karakteristike

- Robustan, ergonomski dizajn
- ClearVision tehnologija za jasnu vidljivost parametara
- Synergic inteligentna kontrola za precizno vođenje parametara
- Širok raspon ulaznog napona – idealno za gradilišta i servisne terene
- **Welding Engineer Mode** za napredne parametre i precizna podešavanja
- **Smart Lift TIG** – čist start luka bez kontaminacije elektrode
- Pouzdane MIG Spot funkcije za precizne tačkaste zavare
- Power Factor Correction (PFC) – manja potrošnja, bolje ponašanje na dužim kablovima
- LED osvetljenje pogonskih točkića i špule
- **ABAP: sistem za balansiran protok zraka (duži vijek ventilacije)**
- Fan on demand – ventilator radi samo kada je potrebno
- VRD sigurnosna zaštita u MMA modu
- Zaštita od pregrijavanja i preopterećenja



Tehnički Podaci

EM-200C		MIG 200 PFC	
Ulazni napon		AC95-265V, 50/60 Hz	
Napon u praznom hodu		AC 115V	AC 230V
MIG	Nazivna ulazna struja	41.8A	38.3A
	Efektivna struja (I _{eff})	17.4A	13.5A
	Nazivna ulazna snaga	3.68kVA	5.74kVA
	Raspon struje	30-140A	30-200A
	Radni ciklus @ 40°C	25%	
	Brzina uvlačenja žice	2-13m/min	2-15m/min
MMA	Veličina špule žice	D200	
	Nazivna ulazna struja	28.5A	25A
	Efektivna struja (I _{eff})	15.5A	13.6A
	Nazivna ulazna snaga	3.28kVA	5.77kVA
	Raspon struje	20-110A	20-180A
	Radni ciklus @ 40°C	25%	
TIG	Nazivna ulazna struja	23.7A	19.1A
	Efektivna struja (I _{eff})	13.3A	10.6A
	Radni ciklus @ 40°C	2.79kVA	4.43kVA
	Raspon struje	5-140A	5-200A
Radni ciklus @ 40°C		25%	
Efikasnost		84%	
Faktor snage		0.99	
Potrošnja u mirovanju		<50W	
Klasa zaštite		IP23S	
Klasa izolacije		H	
Dimenzije (DxŠxV)		565 x 220 x 415mm	
Težina		16Kg	
Preporučena snaga agregata		5.5kVA	8.5kVA

* agregat mora imati AVR regulator



Štandardna Oprema

- MIG gorionik 3m
- Masa kabal 3m
- Crijevo za plin

Opcionalna Oprema

- Bežični daljinski upravljač
- Žični daljinski upravljač